

Audrey A5 TOUCH POS SYSTEM STYLISH POS



The A5 is reflection of Partner Tech's future vision of the POS with complimentary stylish features and innovation design. A technology rich solution that offers industrial grade performance with a high-quality design will make a dramatic statement in your store's environment. The A5 transcends all verticals with Intel processors ranging from SKYLAKE and KABYLAKE platforms, advanced RAM and SSD options gear towards optimizing performance in a feature rich solution. This coupled with the slim and sleek look distinguishes itself from the traditional POS solutions offered in the market today.

SPECIAL FEATURES

- 15.6" Wide Screen All in one POS with FHD resolution and PCT
- Latest SKYLAKE / KABYLAKE High performance Intel CPU with Fanless Design
- Front Panel IP65, Whole Device IP54 Certified
- Maintenance and Service Friendly Design
- High speed M.2 PCIe SSD
- Support up to 3 independent Displays (Operation, Customer facing display and Digital Signage)
- Slim and Stylish Design for retail and hospitality

OPTIONAL

- MSR, IC Card Reader, Fingerprint, RFID, i-Button, VFD, Camera
- 7", 11.6", 15.6" 2nd displays

A5

Item	A5
Display	15.6", Resolution 1366 x 768 / 15.6" Resolution 1920 x 1080 (Optional)
Touch	15.6" Pcap Touch
CPU	Intel® Core™ i5-6300U Processor (SKYLAKE-U Co-lay) Intel® Core™ i3-6100U Processor (SKYLAKE-U Co-lay) Intel Celeron Processor 3955U (SKYLAKE-U Co-lay) Intel Celeron 3965U (KABYLAKE-U Co-lay) Intel® Core™ i3-7100U (KABYLAKE-U Co-lay) Intel® Core™ i5-7300U (KABYLAKE-U Co-lay)
Memory	2 x 260 pin DDR4 SO-DIMM-2133 vertical type, Standard Spec: 4GB, 8GB, 16GB
Storage	M.2 PCIe SSD, 128G / 256G
External I/O Interface	2 x Serial ports, RS232 (RJ45), 0V/5V/12V selection by BIOS (COM1, COM2) 2 x LAN, (IEEE 802.3 10/100/1000 Mbps Ethernet, RJ45) 1 x RJ11 port supports 2 cash drawers with 24V / 12V by jumper setting 1 x DC+12V out 4 x USB Type-A ports (USB3.0/2.0) 1 x DC +12V input power-jack 1 x Audio (1 * Line-out) 1 x HDMI port 1 x VGA
Optional Powered USB	4 x Powered USB (3x12V + 1x24V, on the stand or on PS-103)
Speaker	1 * Speaker 3W
Optional Peripheral	MSR, IC Card Reader, Fingerprint, RFID, i-Button, VFD, Camera
Display Support	3 Independent Displays (Main Display + VGA + HDMI)
Expansion	Mini-PCIe interface
Intel V-Pro	YES (i5 CPU only)
OS Support	POSReady7 (32-bit / 64-bit, SKYLAKE-U only) Windows10 Enterprise IoT LTSC 64-bit Linux Ubuntu 16.04 / 18.04 64-bit
Adaptor	AC-In 100~240V / DC-Out 12V, 90W / 180W
Mechanical	1. Front Panel IP65, whole system IP54, Fan-less Operation 2. VESA 75 x 75
Dimensions	W392 x H320 x D200mm
Weight	5.5KG

*Specification is subject to change without prior notice



CARE . TRUST . RESPONSIBILITY

TAIWAN E-mail:sales@partner.com.tw
USA E-mail:sales@partnertechcorp.com
EUROPE E-mail:info@partner-tech.eu
UK E-mail:sales@partnertechuk.com
CHINA E-mail:sales@partnertech.com.cn

SOUTH AFRICA E-mail:sales@partnertech.co.za
MIDDLE EAST E-mail:info@partnertechme.com
AUSTRALIA E-mail:sales@partner-tech.com.au
SOUTH EAST ASIA E-mail:ptse@partner.com.tw
JAPAN E-mail:sales-jp@partner.com.tw